

PolyPro 3000T Gloss

Permanent labels

Thermal Transfer

Description

A gloss white topcoated biaxially oriented polypropylene film suitable for thermal transfer printing with Zebra's 5095 ribbon.

This product is supplied with a general purpose, permanent acrylic adhesive which offers good adhesion to a variety of surfaces.

Suggested Applications

- Pallet wrap labels
- Recyclable labels with polypropylene substrates
- Shelf edge labels
- Medium-life product and box labelling
- Industrial product labelling

Technical Specifications

	Description	Caliper
Facestock	White topcoated polypropylene film	59 microns
Adhesive	Acrylic based, permanent adhesive	15 microns
Liner	61gsm Glassine liner	56 microns
	Total	130 microns

Recommended Zebra printers: mid-range and high-performance thermal transfer printers

Recommended Zebra ribbons: 3200, 4800, 5095

Minimum application temperature: 5°C

Service temperature range: -20°C to 80°C

Recommended storage conditions: One year duration when stored at approx 20C 50% RH



Facestock Tensile Strength:

- Machine direction 180 MN/m²
- Cross direction 150 MN/m²

Results according to test method DIN 53455

NOTE: For guidance only, not to be used for setting specifications

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order SAMPLE65666.

